

JIB
Two (2) stage hydraulic

ENGINE

Perkins 104.22KR water cooled diesel
50 HP at 2800 rpm

TYRES

Front - 8.25-15 Industrial Cheng Shin 14 ply
Rear - 6.50-10 Industrial Cheng Shin 10 ply

HYDRAULICS

Dantoss hydraulic motors at each front wheel
Infinite variable speed control

SPEED

Maximum road speed 18 KPH

TURNING RADIUS

2.6 metres

SAFETY DEVICES

Winch
Boom lifting
overcentre valve
Boom lifting
overcentre valve
Boom extension
overcentre valve

STANDARD FEATURES

- Hydraulic Winch
 - 1.8 metre fly jib extension
 - 2.8 metre fly jib extension
 - Two person man basket
 - Pallet lifting attachment
 - Rhinohorn
- All options available as factory or field fit.

WARRANTY

1200 hours or 12 months, whichever occurs first

DIMENSIONS

Length	5.15 metres
Width	1.87 metres

Height boom
in horizontal
1.6 metres

Height to top of cab	1.9/5 metres
Gross weight	3.8 tonnes

0.1502 Counterweights (3) 1.42 tonnes

Counterweights (3)

FOR NATIONAL SALES AND SERVICE CONTACT:
Phone: 61 07 3376 2470 Fax: 61 07 3376 2470

Phone: 61 07 3376 2470 Fax: 61 07 3376 2470

YOUR LOCAL SALES AND SERVICE AGENT IS:

MANUFACTURED BY: SKAT INDUSTRIES PTY LTD ACN 075 019 751

„SKAT 2.6 TON MINI CRANE“

WARNING

Safe Working Loads are based on 66.7% of tipping. SWL's are based on firm level ground with 3° deviation for out of level use. For use beyond this point, contact the manufacturer. Weight of hook block and lifting gear to be added to weight of load. During pick and carry, load shall be carried with minimum boom length and as close to ground as possible, at speed not in excess of 3kph. With rhin horn attached, 65mm must be added to boom length indicator reading.

Lower winch before extending boom.
There is no hoist rope compensation on boom extension.

